

# STARTRITE



**COMBINED PLANER & THICKNESSER  
MODEL PT 260**

# Constructional details

The Startrite PT260 is robustly built and attractively finished in durable stove enamelled paint. Cast iron planer tables are suitably ribbed for strength and rigidity, with ground surfaces for accuracy.

A two knife steel planer block runs in sealed-for-life ball bearings for trouble free performance and deflector plates protect the infeed and outfeed rollers from the shavings.

All electrical and working parts are contained within the steel base unit which incorporates provision for bolting the machine down if required. Internal wiring is connected for ready for use. Only mains supply to switch panel is required to put this quantity machine into use.

## Specification

	Imperial (Approx.)	Metric (Accurate)
Surface Capacity	10¼"	260mm
Combined table length	39¾"	1000mm
Infeed table width	13½"	345mm
Outfeed table width	10¾"	265mm
Rebate depth	9/16"	15mm
Cutterblock diameter	2¾"	70mm
Cutterblock speed	6000 r.p.m.	6000 r.p.m.
Number of cutters	2	2
Thickening depth	7"	180mm
Thickening width	10¼"	260mm
Thickening table length	22"	560mm
Feed speed	18.7 ft/min	5.7 m/min
Motor power	3 phase	1.5 H.P. 1.1 K.W.
	1 phase	1.5 H.P. 1.1 K.W.
Machine dimensions	Length	39¾"
	Width	23¾"
	Height	39"
Weight	265 lbs.	120 Kg.

## Standard equipment:

- Planer Fence tilts to 45°
- Rear Fence Guard.
- Cutterblock Bridge Guard.
- Thickening Guard and Chip Deflector.
- Rebate Safety Holding Device.
- Pair H.S.S. Planer Knives.
- Totally Enclosed Motor.
- Push button switchgear with overload and no-volt protection.
- Instruction Manual.



### Surfacing

Lever action infeed table enables rapid adjustment to be made against scale. Safety type cutterblock with two H.S.S. knives easily adjusted.



### Thicknessing

Thicknessing table supported on large diameter column. Raised and lowered by means of handwheel and lockable against easily read scale, calibrated in Imperial and Metric units.



### Rebating

Large capacity rebates can be performed. Lever action on infeed table allows rapid change to depth required. Safety holding device fitted as standard.



### Bevelling

The large, rigid and easily adjusted fence allows bevels and chamfers up to 45° to be cut.

**STARTRITE MTC**

Startrite Machine Tool  
Company Ltd

Waterside Works, Gads Hill,  
Gillingham, Kent ME7 2SF  
Telephone: (0634) 281281  
Telex: 965730 Fax: (0634) 281401

THE 600 GROUP

Description and specification do not form part of a contract and are subject to change without notice.